APPLICATION UNDER UNITED STATES PATENT LAWS

Invention: COMPUTER SYSTEM FOR IDENTIFYING LOCAL RESOURCES

Inventor(s):   PHELAN, Sean

Pillsbury Madison & Sutro LLP
Intellectual Property Group
1100 New York Avenue, N.W.
Ninth Floor, East Tower
Washington, D.C. 20005-3918
        Attorneys
Telephone: (202) 861-3000

<u>This is a</u>:

[ ] Provisional Application

[ ] Regular Utility Application

[ ] Continuing Application

[XX] PCT National Phase Application

[ ] Design Application

[ ] Reissue Application

[ ] Plant Application

[ ] Substitute Specification
     <u>Sub. Spec</u> filed _____
          in App. No. ____/_____

SPECIFICATION

COMPUTER SYSTEM FOR IDENTIFYING LOCAL RESOURCES

Background of The Invention

This invention relates to computer systems, and to methods of operating computer systems. The invention has

5   particular relevance to the so called "World Wide Web", which is part of the global computer network system known as the Internet.

Description of Related Art

The Internet and the World Wide Web ("WWW" or "The Web") have been described in great detail in a large number

10   of publications in recent months. The Web consists essentially of an enormous number (at the last count, many millions, and expanding rapidly) of "host" or "server" computers which contain information of various types which users may wish to access. Users of the system employ a

15   "client" computer, running "client" software, in order to access the information. Such client programs are usually known as "browsers".

Various standard protocols enable requests to be formulated by the many client computers, and passed via the

20   Internet to whichever computer holds the relevant information, which then returns the information to the client, using the same protocols.

The protocol which is used on the World Wide Web is an agreed standard, known as the HyperText Transfer Protocol

25   (HTTP).

The language in which "Web" pages are generated is known as "HyperText Markup Language" (HTML).

The success of HTML/HTTP is based to a large extent on the ability of HTTP to produce so called "hypertext links"

30   in the form of some sort of displayable icon on the computer screen of the client. The icon may be a graphical icon, or, more commonly, simply text represented in a form which is visually distinct from the surrounding text. Activating the icon with a pointing device (for example,

35   clicking on it with a mouse pointer) causes the browser software to formulate a request for further information to

2

be sent to the "client". This further information may be simply a "page" of text data, or it may be graphical data, or sound or video data. It may reside on the same server computer as the page containing the hypertext link, but

5   need not do so, and will often reside on a computer many thousands of miles away.

The World Wide Web has recently attracted increasing attention as an advertising medium for various goods and services. The advantage of the Web as an advertising

10   medium is that a single connection allows access by millions of potential customers around the world, without any need for the customers to know or be interested in the physical location of the server computer which is providing the information. Links to the pages of interest may be

15   provided by hundreds or thousands of other pages, provided on other servers, throughout the world.

For many goods and services, the lack of a physical "place" on the Internet is an advantage. A consumer, no matter where his location, is presented with a familiar

20   interface, which makes access very straightforward. The very size of the World Wide Web however, means that, as presently constituted, it is not well suited to answering questions about places and proximity. For example, it is not possible, using existing Web search tools to answer

25   questions such as "where is the nearest hamburger restaurant?" in spite of the enormous benefit which would accrue to major restaurant chains and the like in providing their own answers to such questions, with the speed and ease for which the Internet is famous.

30   The present invention seeks to address the problem of facilitating access by Internet users, and in particular by users of the World Wide Web, to Internet resources, where the primary differentiator between different places of interest is geographical.

35   According to a first aspect of the present invention, there is provided a method of operating a computer system,

the method comprising the steps of:

storing on a map server computer map data representative of a map of a geographical area;

storing on the map server computer coordinate data

5   indicative of the spatial coordinates of at least one point associated with the geographical area represented by the map, so as to enable correlation of points on the map with their corresponding geographical location;

storing on an information server computer information

10   data relating to at least one place of interest within the geographical area, said information data including data representative of the spatial coordinates of the place of interest within the area;

transmitting a map request to the map server computer

15   from a client computer, and transmitting from the map server computer to the client computer in response to the map request the map data and the coordinate data associated with the area represented by the map;

~~utilising~~ *utilising* the ~~map~~ *map* data to display an image of the map

20   on a visual display unit associated with the client computer;

transmitting an information request to the information server computer from the client computer, and transmitting from the information server computer to the client computer

25   in response to the information request the information data relating to at least one place of interest within the geographical area; and,

displaying the information data relating to at least one place of interest on the visual display unit.

30   The map request may be transmitted before the information request, the information request being formulated by including coordinate data provided by the map server.

The information request may be transmitted before the

35   map request, the map request being formulated by including coordinate data provided by the information server.

According to a second aspect of the present invention, there is provided a computer system, the computer system comprising:

a map server computer for storing map data
5 representative of a map of a geographical area and coordinate data representative of the spatial coordinates of at least one point lying within the area represented by the map;

an information server computer for storing information
10 data representative of at least one place of interest within the geographical area, said data including data representative of the spatial coordinates of the place of interest within the area; and,

a client computer, the client computer having a visual
15 display unit;

wherein the client computer includes

means for transmitting a map request to the map server computer to request transfer to the client computer of the map data and the coordinate data
20 associated with the area represented by the map,

means for displaying an image of the map on the visual display unit, and

means for transmitting an information request to the information server computer to identify places of
25 interest known to it and lying within the geographical area,

wherein the information server computer includes means for transmitting to the client computer in response to the information request the data representative of at least one
30 place of interest within the geographical area, and

wherein the client computer includes means for displaying said data associated with the place of interest on the visual display unit.

The order in which the map server and information
35 server are mentioned above is not meant to imply any particular restriction as to the order in which the servers

are accessed by the client. As with any Web search, either server could be accessed first. A link provided initially by the information server may link directly to a map server in accordance with the invention, for example.

5   In a preferred embodiment, a client device which has the capabilities of both a cellular telephone and a Web browser may pass the names and/or geographical coordinates of its surrounding cellular base stations to the map and/or overlay server computers. Such location information may be

10   utilised by the map server computer to deliver a map of the current location of the client device, and/or by the overlay server computer to identify facilities near to the current location of the client device.

       The information relating to the place of interest may

15   be superimposed or overlaid on the map image at a position on the image corresponding to the location of the place of interest on the map. Thus, for example, the information (or "overlay") server may contain details of, for example, hotels, restaurants, shops or the like, associated with the

20   geographical coordinates of each location. The map server contains map data, including coordinate data representing the spatial coordinates of at least one point on the area represented by the map. Further data is also required, so as to enable correlation of points on the map with their

25   corresponding geographical location. Such further data may be, for example, the coordinates of an additional point on the map. Preferably, the map's scale and overall dimensions are included. Alternatively, coordinates of two opposite corners of the map are included. As a further

30   alternative, the said further data may include a simple scale factor and a direction factor.

       In a further preferred embodiment, the map server may be provided with a list of categories of places of interest, together with details of the respective

35   information servers on which further information about each category is located. Each of these categories may be

associated with a respective icon on the VDU of the client. In an alternative embodiment, such a list of categories may be provided on a further server.

In an embodiment, initially, the client computer may
5 display the map as a simple outline, with no superimposed icons. When one of the "category" icons is activated (for example, by clicking with a mouse or other pointing device), the client computer formulates a request to the appropriate information server for the information server
10 to supply a list of locations known to it which lie within the rectangle defined by the said coordinates. The information supplied by the information server may include textual, graphical, sound, video or other information, and may include additional hypertext links to other locations
15 or facilities on the Web, which themselves may include textual, graphical, sound, video or other information.

It is a particular advantage of the system that the various information servers do not need to have knowledge of the map server software provided on the map server, and
20 vice versa. All that is required in order for the relevant data to be supplied to the client computer is a consistent protocol for providing the coordinates of the various places of interest.

Two or more information servers can provide "places of
25 interest" data independently, without either having any knowledge of the other. For example, one server may provide locations of hotels, a second may provide locations of restaurants, and a third may provide locations of print shops or the like. All of the data (for example, hypertext
30 links, icons etc.) can be overlaid on a single map on the screen of the client computer with hypertext links provided to the various source data on the different overlay or information server computers.

In a particularly preferred embodiment, the client
35 computer may include locating means for establishing the current geographical location of the client computer. This

may be by means of a satellite system such as the Global
Positioning System. The client computer preferably
includes means for passing the said location information to
the information server computer. Such location information

5   may be utilised by the information server computer to
identify facilities within a given radius of the current
geographical location of the client computer. This
facility makes the method of the invention of particular
usefulness to portable computer systems.

10   The client computer may include means for scrolling or
zooming the map image, to display an image of a different
geographical area, and means for varying the displayed data
relating to the places of interest, so as to take account
of the change in the display geographical area. This may

15   take the form simply of changing the position of the icon
or hypertext data relating to particular points of
interest, so as to take account of the change in the
display geographical area. Preferably, however, the client
computer may include means for formulating a further

20   request to an information server, to identify places of
interest lying within the new geographical area.
         An embodiment of the present invention will now be
described by way of example with reference to the
accompanying drawings, in which:

25   Figure 1 is a graphical representation of a client
screen, showing a simple map with "category" icons;
         Figure 2 shows the same map after retrieval of
information relating to various places of interest (in this
case, hotels and restaurants); and,

30   Figure 3 is a schematic representation of information
flow between the map and overlay servers and the client
computer.
         Referring to Figure 1, the screen 1 of a client
computer 10 is shown, as generated by an HTML document.

35   The screen 1 contains three windows or frames: a "map"
frame 2, a "navigation" frame 3 containing buttons 4 for

8

zooming and panning the map, and an "info" frame 5 which
controls the display of overlay information on the map.

5   The overall information flow is indicated graphically
in Figure 3. A map request to a map server computer 11
from the client computer 10 specifies the geographical
coordinates of the map, which may be the bottom left corner
of the map and the top right corner of the map or centre
point and scale, for example. The coordinates may be
supplied to the map server 11 as the latitude and longitude
10   in degrees of the centre point of the map and its scale,
for example.

The map is supplied by the map server 11 in a map
response in any of the various conventional graphics
formats, for example in "GIF" or "JPEG" format. In a
15   preferred embodiment, the map server 11 will also return
the coordinates covered by the map, but this is not
essential as they may be inferred from the map request.

Also supplied by the map server 11 are the icons
6,7,8,9, which are displayed within the "info" frame 5.
20   Icon 6 indicates banks, icon 7 restaurants, icon 8 hotels,
etc. Information relating to each category of facilities
(banks, restaurants, hotels, etc.) is held on an
information server computer 12. The information server
computers 12 for the different information categories may
25   be the same or different.

Clicking with the mouse on a respective icon 6-9
causes the client computer 10 to formulate an information
request, which may be in the form of a standard Web URL
(Uniform Resource Locator) including additional protocol
30   elements relating to the location which the user wishes to
search.

An important feature of the present invention is the
addition of a universally recognised standard for
geographic reference (i.e. longitude and latitude) to the
35   protocols and standards of the Internet and the World Wide
Web, and its use to combine data from mutually independent

sources.

Information requests produced by the client computer
10 may be of various forms, provided that a protocol is
provided for the exchange of the geographical coordinate
5   data.

Figure 3 shows the two key transaction types used by
the client 10. One transaction type consists of the
information request, which goes to a provider of
information to be overlaid on a map, such as an information
10   server computer 12, followed by a response from that
provider 12. The other transaction type is a map request,
which goes to a map server computer 11, followed by a map
response back to the client 10.

Both request types take the form of Uniform Resource
15   Locators (URLs) which are transmitted in the same way as
any other WWW request. Unlike other URLs, the map and
information requests contain longitude and latitude
information which specify the request's geographical
coverage.

20   In a preferred embodiment, the responses also contain
longitude and latitude information, but this is not
essential as they may be inferred from the requests.

In a simple embodiment, the information response from
the overlay or information server 12 consists of an HTML
25   document. This document contains HTML tags specifying one
or more overlay icons and their screen positions. It also
specifies the map to be displayed underneath the icons.

In a more advanced embodiment, suitable for client
browsers capable of running Java or some other local
30   processing capability, the response from the information
server 12 specifies one or more overlay icons and
associates a longitude and latitude with each. Longitude
and latitude are resolved to screen position by a Java
Applet or other locally executed program.

35   The most important difference between the simple
embodiment and the advanced embodiment mentioned above is

10

the point at which the longitude and latitude of overlay
icons are resolved to positions on the screen 1 of the
client 10.   Advanced embodiments place this function within
the client browser, where a Java Applet or some other local
5   processing carries out the transformation.   In simple
embodiments, the transformation is carried out in the
information server.   Simpler embodiments are therefore less
powerful and have less platform-independence, but can be
implemented on simple client browsers.

10   The "map request" shown in Figure 3 may take the
following form:

        http://www.multimap.com?lon="-0.1666"
            &lat="51.545"&scale="25000"&xp="500"&yp="300"

15

        This map request contains parameters specifying the
longitude, latitude and scale of the map, and also its
dimensions in horizontal and vertical pixels (xp and yp).
        An "information request" may be of the form:

20

        http://mcdonalds.com/locations.cgi?lat="51.5449"
            &lon="-0.16658"&radius="1.6"

        This is a search request to a server called
25   mcdonalds.com requesting all locations within a one mile
radius of a location in Hampstead, London.
        The map requests and information requests may contain
any number of elements from an expandable list of
parameters, including the following examples:

30

lat=51.5449   Latitude in degrees, as a single real number
lon=-0.16658   Longitude in degrees, as a single real
                number
radius=1.6   Radius in kilometres
35   max=10   Maximum number of locations in search result
xp=500   Horizontal size of the map in pixels

lon=-0.16658	Longitude in degrees, as a single real number
radius=1.6	Radius in kilometres
max=10	Maximum number of locations in search result
xp=500	Horizontal size of the map in pixels
yp=300	Vertical size of the map in pixels
scale=25000	Map scale
vr=0	Virtual Reality level - 0 for "reality", other values specify other "virtual worlds" for testing, simulation or whatever

There are a number of other possible terms that may be included.

In simpler embodiments, the map response is an image file encoded in either GIF or JPEG format, for example. It is sent in the same format as other image files on the Web. In more advanced embodiments, the map response may be take the form of either a raster image or vector data, and may be rendered at the client by a Java Applet or other local processing.

The information response can take one of a number of different forms, depending on the capabilities of the client browser.

In a preferred implementation, the information response takes the form of an HTML document which contains references to one or more overlay icons, each with an associated longitude and latitude, together with a call to a Java Applet or some other form of local processing.

In a simpler implementation, the HTML document may contain the screen positions of the icons as pixel offsets rather than longitude and latitude. In this case the positioning of overlay icons on maps is achieved through the positioning capabilities of other HTML functions such as background images, frames, horizontal and vertical image offsets and others.

An example of such an information response is:

```
<HTML> <BODY background="http://multimap.com?
lon=-0.1666&lat=51.545&scale=25000&xp=500&yp=300">
<imgsrc="icon.gif" hspace=240 vspace=140> </BODY></HTML>.
```
In this example, a map is requested from the map server

5   "multimap.com" and is displayed as a background image, and
the icon in the file "icon.gif" is overlaid at the centre
of the map. Preferably, in order to work correctly, this
"map as background" technique should be implemented within
a fixed-size frame.

10   When the user clicks on one of the subject buttons
6-9, the client 10 establishes a connection to the
information server whose URL is embedded in the button 6-9.
The client 10 sends an information request, as described
above.

15   The information server 12 generates a list of the
entries in its database having a longitude and latitude
within the bounds specified, and uses them to create an
information response, as described above. Each entry is
associated with a displayable name and/or icon and

20   optionally a longitude and latitude. The icons or text may
be highlighted to show further information such as levels
of availability, etc.

         The client software normally overlays the displayable
names and/or icons on its map.

25   The user has the option of opening one or more icons
from the screen, normally by clicking on the displayable
name. This passes the URL to the Web browser which opens
it in the usual manner.

         In Figure 2, the current location has been sent to

30   three servers: one run by a high street bank, which
returns the location of cashpoint machines, one by an
independent hotel reservation system and one by a well-
known fast food chain.

         The result of the responses by the overlay servers 12

35   are shown in Figure 2, in which the same map is displayed
with icons 13 representing the various facilities reported

by the second server 12, and hypertext links 14 to text
pages or other Web facilities, in the usual way.

It should be noted that the client computer 10 may be
used to transmit the information request with geographical
5   data first. The overlay or information server 12 responds
with information data, including coordinate data, relating
to the requested services for example. This data, as well
as being used to generate the display on the client
computer 10, can be used to formulate the map request
10   including coordinate data for transmission by the client
computer 10 to the map server 11. The map server 11 then
responds with the map data, which is then transmitted to
the client computer 10. The map can then be displayed on
the client computer visual display unit and overlaid with
15   graphics representing the information data. In other
words, either the map request or the information request
can be formulated first for transmission to the appropriate
server 11,12.

The architecture of the preferred system is such that
20   it can support a movable map window. A user can scroll
North, South, East or West on the screen and see more
detail appear, and can zoom in and out for more detail or
for a wider perspective using the zoom and move buttons 4.
This also enables a moving display, such as a hand-held
25   device or a rolling map installed in a car, to be
dynamically updated with new locations as the displayable
window moves over them.

Although the client computer 10 may be a stationary PC
connected to the Internet, the architecture is designed to
30   support mobile clients such as car navigation systems and
personal digital assistants (PDAs). The client software
preferably supports direct connection to Global Positioning
System (GPS) receivers, and preferably implements the NMEA
0183 standard for exchange of navigational data. If the
35   client is also a cellular telephone, it preferably supports
the transfer of information derived from the cellular

network. In a preferred embodiment, the client transfers its own position to the information server and map server within the HTTP protocol by adding an HTTP header line to its request messages. In the case that the client is

5 connected to a GPS receiver and therefore knows its exact location, it can add an HTTP header line as follows: remote_position: lon="-0.1666"; lat="51.545". In the case that the client does not have its exact position, but does have access to the name of its nearest cellular base

10 station, it can add an HTTP header line as follows: remote_cellname: LONDON-SW-5. A map server or information server which maintains data on the locations of cellular base stations can convert the cell name to a location and deliver the appropriate map and/or overlay information. In

15 the case that the client is not able to add HTTP header lines as described above, location and/or cell names may be transmitted within other HTTP headers or within the HTML protocol, but such embodiments are not considered preferable. It is important to note that the client will

20 often request information on a location other than its own current location, and that the location of interest is transferred within the Map Request/Information Request URLs, while the client's own location is transferred in the HTTP header. This combination allows the server computers

25 to implement a wide range of additional functions, such as displaying the distance from the current location to the location of interest. In the case that the client's location is known to be changing, such as a cellular phone connected to a GPS receiver, the screen display may be

30 refreshed on a regular basis to show the client's current location. This refresh may be achieved by using the "refresh" function within the HTTP/HTML protocols, or it may be achieved using the local programmability of the client.

35   It is particularly preferred that the additional functionality provided within the World Wide Web, and its

15

architecture, is built within the extensible framework of
HyperText Markup Language (HTML) and the HyperText Transfer
Protocol (HTTP). The extensions to HTML/HTTP are thus
preferably entirely compatible with existing Web standards
5   and do not seek to modify or replace any part of the Web
architecture.

In a preferred embodiment, the functionality described
above is added to the client computer 10 by providing
additional software for a known Web browser (for example,
10   Netscape, Mosaic, etc.). This software may be implemented
as separate programs (i.e. a "helper application"), or as
plug-in programs that execute within a browser program, or
as Java Applets which are downloaded and executed as
required.

15   Alternatively, a subset of the full functionality may
be implemented using the browser's standard display and
positioning capabilities only. An implementation of the
latter case requires greater functionality in the
information server, and is a preferred implementation in
20   circumstances where it is difficult or impossible to add
functionality to the client browser.

The server computers 11,12 may employ well-known
standard database tools in conjunction with known Web
server packages, in order to recognise the requests and
25   generate the responses described above.

Another important feature of the present invention is
that maps and overlay information can be "persistent".
That is, pointers to maps or places can be stored in
databases on the client computer 10 and become a permanent
30   feature of displays. A typical use of this feature would
be to store the user's home location and display it on any
map covering that location.

In a preferred embodiment, persistent locations are
stored using the extensions to HTTP known as "magic
35   cookies". The magic cookie parameters used are based upon
the request parameters listed above, i.e.:

Set-Cookie: Home="lon=-0.1666&lat=51.545";

   Software may be provided for the conversion of postal
codes (zip codes) into longitude and latitude information.
5 Software may be provided for the conversion of full or
partial addresses into longitude and latitude information.
This software is normally provided on the map server 11; in
this case, the user enters an address or postcode in a form
and sends this to the map server. The map server responds
10 with an HTML document containing longitude and latitude,
and the user receives a map of the locality of the address
or postcode. Alternatively, such software can be provided
on the client computer 10.
   The system and method of the present invention avoids
15 the classic problems of Geographic Information Systems
(GISs) by imposing a single, standardised geographic
reference model, and restricting data exchanges to those
classes of geographic information which can conform to the
reference model.
20 Because of this, servers providing information do not
have to deal with maps, map ownership issues or mapping
software, and information from several different sources
can be integrated on a single screen.
   It is of course envisaged that the invention may be
25 implemented in ways which are different from the ways
specifically exemplified above. For example, the
coordinate data embodied in the map and facility
information may be presented in ways other than in absolute
latitude and longitude format.
30 Embodiments of the present invention have been
described with particular reference to the examples
illustrated. However, it will be appreciated that
variations and modifications may be made to the examples
described within the scope of the present invention.